

Wall Mounted Lifestyle & Designer Ranges

Why choose our Lifestyle & Designer Ranges?


Both ranges combine a sleek, modern finish with efficient, intelligent features to blend seamlessly with any home's interior. The Lifestyle Range has a matte finish and smooth edges and the Designer Range is very compact at just 185mm deep.

Ease of use

All models across the Lifestyle and Designer Ranges are accompanied by a simple and easy to use controller, giving you control over the indoor comfort of your home/ workplace, right at your fingertips. With features such as low noise mode, economy operation and program timers, you can tailor your comfort needs at the touch of a button.

Energy efficiency

The Lifestyle and Designer Range models are some of the most energy efficient heating/cooling systems Fujitsu has designed. With built-in features such as high efficiency DC componentry, high density multi-path heat exchangers and other energy management features



ASTG09KMTC

including human sensor control, economy mode and weekly timers, your home will be more comfortable and affordable all year round.

Human sensor control

All models in the Lifestyle and Designer Ranges contain human sensor control, an intelligent feature which detects movement of people to deliver optimum efficiency and temperature control.

When in operation, if the sensor detects no movement in a room after 20 minutes, the unit will automatically switch to energy saving operation, modifying temperature to minimise energy consumption. When movement is detected within the room, the unit reverts back to its previous setting.





Air Filters

Fujitsu's Apple-Catechin filters contribute to a fresher and cleaner living environment.

Why choose Fujitsu?



Specialist expertise



Advanced Air Filters



New Zealand's only accredited installation programme



6 Year Manufacturer's Warranty*



Trusted brand





*6 year warranty applies when the unit is installed by a Fujitsu Accredited Installer. Register your warranty easily online at: fujitsugeneral.co.nz/help-centre/ warranty-registration



Lifestyle Range

KMTC models

Indoor units



Standard Controller

ASTG09/12KMTC

stra

ASTG18/22/24KMTC



ASTG30/34KMTC

Optional controllers



anywAiR[®] in-built Wi-Fi

adaptor UTY-FGAN1





Touch Panel

Controller*

UTY-RNRYT5







Wi-Fi

device











AOTG18/22/24KMTC




AOTG30KMTC



AOTG34KMTC

Product specifications:

Set Code				SET- ASTG09KMTC	SET- ASTG12KMTC	SET- ASTG18KMTC	SET- ASTG22KMTC	SET-ASTG24KMTC	SET-ASTG30KMTC	SET-ASTG34KMTC
Model No.	Indoor unit			ASTG09KMTC	ASTG12KMTC	ASTG18KMTC	ASTG22KMTC	ASTG24KMTC	ASTG30KMTC	ASTG34KMTC
Model No.	Outdoor unit		AOTG09KMTC	AOTG12KMTC	AOTG18KMTC	AOTG22KMTC	AOTG24KMTC	AOTG30KMTC	AOTG34KMTC	
Operation Type				Reverse Cycle	Reverse Cycle	Reverse Cycle				
Power Source	ource V / Ph / Hz			240 / 1 / 50	240 / 1 / 50	240 / 1 / 50	240 / 1 / 50	240 / 1 / 50	240 / 1 / 50	240 / 1 / 50
Capacity	Cooling		kW	2.50 (0.80 - 3.60)	3.50 (0.80 - 4.10)	5.00 (1.00 - 6.50)	6.00 (1.10 - 7.50)	7.10 (1.10 - 8.30)	8.50 (2.90 - 10.50)	9.40 (2.90 - 11.20)
	Heating		kW	3.20 (0.90 - 5.30)	3.70 (0.90 - 6.10)	6.00 (1.05 - 8.70)	7.20 (1.10 - 9.40)	8.00 (1.10 - 10.10)	9.00 (2.20 - 11.20)	10.30 (2.70 - 11.70)
Input Power	Cooling		kW	0.53 (0.15-1.04)	0.89 (0.15-1.29)	1.16 (0.24-1.68)	1.58 (0.24-2.30)	2.08 (0.24-3.15)	2.46 (0.58-3.85)	2.78 (0.59-4.03)
	Heating		kW	0.66 (0.25-1.61)	0.79 (0.25-1.89)	1.28 (0.14-2.42)	1.70 (0.14-2.63)	1.91 (0.14-3.00)	2.34 (0.50-4.01)	2.84 (0.60-4.24)
EER	Cooling		kW/kW	4.71	3.93	4.31	3.80	3.41	3.45	3.38
COP	Heating		kW/kW	4.84	4.68	4.69	4.24	4.19	3.84	3.63
Star Rating	Cooling: Hot / Average / Colo		old	5.5 / 5 / 5.5	4.5 / 4.5 / 5	4.5 / 4.5 / 4.5	4/4/4	3.5 / 3.5 / 3.5	3/2.5/2.5	3/2.5/2.5
	Heating: Hot / Average / Co		old	3.5/3/3	3.5 / 3 / 2.5	3/2.5/2.5	3/2.5/2	3/2.5/2	2.5/2/2	2/2/1.5
Running Current	Current Cooling / Heating		amps	3.0 / 3.5	4.2/4	5.1 / 5.6	6.8 / 7.4	8.9 / 8.3	10.4 / 10.1	11.7 / 11.9
Moisture Removal			1/hr	0.3	1.0	1.3	2.3	2.7	2.5	3.5
Noise Level	Indoor Sound Pressure	Cooling	dBA	40 / 19	40 / 19	46 / 29	48/29	49 / 29	51 / 33	52 / 34
	(High / Quiet)	Heating	dBA	40 / 21	42 / 21	46 / 29	48/29	49 / 29	51 / 33	51 / 33
	Outdoor Sound Pressure Cooling / Heating		dBA	46 / 46	49 / 49	47 / 48	49 / 52	54 / 52	50 / 54	50 / 54
	Outdoor Sound Power		dBA	55	59	59	61	66	66	65
Air Circulation (Indoor - High Fan) Cooling / Heating		1/sec	194 / 197	194 / 214	283 / 283	294 / 294	325 / 325	389 / 389	389 / 389	
Net Dimensions H x W x D	Indoor Unit		mm	270 x 834 x 222	270 x 834 x 222	280 x 980 x 240	280 x 980 x 240	280 x 980 x 240	340 x 1,150 x 280	340 x 1,150 x 280
			kgs	10	10	12.5	12.5	12.5	18.5	18.5
	Outdoor Unit		mm	542 x 799 x 290	542 x 799 x 290	716 x 820 x 315	716 x 820 x 315	716 x 820 x 315	830 x 900 x 330	914 x 970 x 370
			kgs	32	32	42	42	42	60	74
Piping Connections (Liquid / Suction) mm			mm	Ø6.35 / Ø9.52	Ø6.35 / Ø9.52	Ø6.35 / Ø12.70	Ø6.35 / Ø12.70	Ø6.35 / Ø12.70	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88
Max Pipe Length (Precharged length) m			m	20 (15)	20 (15)	30 (15)	30 (15)	30 (15)	75 (20)	75 (30)
Max Height Difference m			m	15	15	25	25	25	30	30
Operation Range	Cooling		°CDB	-10 to 46	-10 to 46	-10 to 46				
	Heating		°CDB	-15 to 24	-15 to 24	-15 to 24				
Refrigerant			R32	R32	R32	R32	R32	R32	R32	



Designer Range

KUCA models

Optional controllers



anywAiR[®] infra-red Wi-Fi device












Indoor unit



Standard ASTG09/12/18KUCA Controller

Outdoor units







AOTG18KUCA



Product specifications:

Set Code				SET-ASTG09KUCA	SET-ASTG12KUCA	SET-ASTG18KUCA	
Ma dal Nia	I	ndoor unit		ASTG09KUCA	ASTG12KUCA	ASTG18KUCA	
Model No.	0	utdoor unit		AOTG09KUCA	AOTG12KUCA	AOTG18KUCA	
	Operation '	Туре		Reverse Cycle	Reverse Cycle	Reverse Cycle	
Power Source	,	V / Ph / Hz		240 / 1 / 50	240/1/50	240/1/50	
Connection	Cooli	ng	kW	2.50 (0.90-3.60)	3.50 (0.90-4.10)	5.00 (0.90-6.00)	
Capacity	Heati	ng	kW	3.20 (0.90-5.40)	4.30 (0.90-5.70)	6.00 (1.05-7.50)	
	Cooli	ng	kW	0.51 (0.25-1.14)	0.88 (0.25-1.38)	1.31 (0.21-2.20)	
Input Power	Heati	ng	kW	0.67 (0.25-1.60)	1.06 (0.25-1.70)	1.58 (0.20-3.10)	
EER	Cooling		kW/kW	4.90	3.98	3.82	
COP	Heating		kW/kW	4.78	4.06	3.80	
Star Rating	Cooling: H	lot / Average / Co	old	5/4/4	4/3.5/3.5	4/3.5/3.5	
	Heating: I	Hot / Average / Co	old	3.5/3/2.5	3/2.5/2	2.5/2/1.5	
Running Current	unning Current Cooling / Heating			2.7 / 3.3	4.3 / 4.9	5.6 / 6.7	
Moisture Remo	val		I/hr	1.3	1.8	2.6	
	Indoor Sound Pressure (High / Quiet)	Cooling	dBA	42 / 21	43 / 21	47 / 29	
		Heating	dBA	42 / 21	43 / 22	46 / 29	
Noise Level	Outdoor Sound Pressure Cooling / Heating		dBA	47 / 47	49 / 49	51 / 48	
	Outdoor Sou	nd Power	dBA	57	63	65	
Air Circulation (In	door - High Fan) Cool	ing / Heating	1/sec	222	236	264	
			mm	282 x 870 x 185	282 x 870 x 185	282 x 870 x 185	
Net	Indoor	Unit	kgs	9.5	9.5	9.5	
Dimensions H x W x D	0.11		mm	540 x 790 x 290	540 x 790 x 290	620 x 790 x 290	
	Outdooi	Unit	kgs	34	34	40	
Piping Connecti	ions (Liquid / Suctio	(Liquid / Suction)		Ø6.35 / 9.52	Ø6.35 / 9.52	Ø6.35 / 12.70	
Max Pipe Length (Precharged length) m				20 (20)	20 (20)	20 (20)	
Max Height Difference				15	15	15	
Operation	Cooli	ng	°CDB	10 to 46	10 to 46	10 to 46	
Range	Heati	ng	°CDB	-15 to 24	-15 to 24	-15 to 24	
	Refrigera	int		R32	R32	R32	

For more product information, please visit fujitsugeneral.co.nz. Due to ongoing research and development, specifications and designs are subject to improvement without notice therefore relevant manuals must be consulted before any action is taken to install or service these products. All capacity and energy efficiency ratings are based on the 2019 GEMS <65kw determination. Running current is at rated conditions (AS/NZS 3823) and does not include compressor start-up or variations in power supply and load conditions.



^{*}Requires Communication Kit.





Control your Fujitsu Heat Pump anytime, anywhere by smartphone and tablet



AC control Switch unit on

or off

Mode Easily switch between cooling and heating

Setpoint To Adjust temperature set point

Room ambient To Monitor your room's temperature

Fan speed Adjust the fan speed remotely

Easily operate your Fujitsu Heat Pump/Air Conditioning unit anywhere by smartphone and tablet. The anywAiR® technology Wi-Fi device allows you to remotely control your Heat Pump/Air Conditioner using the free and easy to use **myanywAiR App.** The device is compatible with a range of Fujitsu Heat Pump/Air Conditioner units* up to 10 years old with an infrared receiver.

To find out more, please visit myanywair.com.

For Lifestyle KMTC, anywAiR® in-built WiFi adaptor is available. Please ask for more details.

Apple, the Apple logo, iPhone and Siri are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. ©2021 Google LLC All rights reserved. Google Play and the Google Play logo are trademarks of Google LLC. Other trademarks and tradenames are acknowledged to be the copyright of their respective holders.





NEW ZEALAND'S FAVOURITE AIR®

FUJITSU GENERAL NEW ZEALAND A SUBSIDIARY OF FUJITSU GENERAL LIMITED

fujitsugeneral.co.nz 04 568 876 contact@fujitsugeneral.co.nz

Fujitsu General accepts no liability for incorrect data.
Please ensure you have confirmed installation requirements and pipe sizes prior to install.